

Exabeam EX2003

Hardware Specifications

Publication date July 24, 2020

Exabeam

2 Waters Park Dr. Suite 200
San Mateo, CA 94403

650.209.8599

Have feedback on this guide? We'd love to hear from you!
Email us at docs@exabeam.com

Disclaimer: Please ensure you are viewing the most
up-to-date version of this guide
by visiting the [Exabeam Community](#).

Copyright

All content in this document, including text, graphics, logos, icons, images, and video clips, is the exclusive property of Exabeam or its content suppliers and is protected by U.S. and international copyright laws. The compilation (meaning the collection, arrangement, and assembly) of all content in this document is the exclusive property of Exabeam and is also protected by U.S. and international copyright laws. The content in this document may be used as a resource. Any other use, including the reproduction, modification, distribution, transmission, republication, display, or performance, of the content in this document is strictly prohibited.

Copyright ©2020 Exabeam, Inc. All Rights Reserved.

Trademarks

Exabeam, the Exabeam logo, Threat Hunter, Smarter SIEM, Smart Timelines and Security Management Platform are service marks, trademarks or registered marks of Exabeam, Inc. in the United States and other countries. All other brand names, product names, or trademarks belong to their respective owners. The marks and logos displayed in this document may not be used without the prior written consent of Exabeam or their respective owners.

Patents

Exabeam owns, and reserves all rights for, patents for Exabeam products and services, which may be protected under registered patents as well as patents pending.

Other Policies

For information regarding Exabeam's treatment of personally identifiable information, please review Exabeam's current privacy policy at www.exabeam.com/privacy.

Table of Contents

1. EX2003 Hardware Specifications	5
---	---

1. EX2003 Hardware Specifications

This type of appliance is to be used for the following Exabeam products: Advanced Analytics and Incident Responder, exclusively for the following node types:

- Advanced Analytics worker node and Entity Analytics
- LIME node
- Node for Case Manager and Incident Responder

If you have questions about this appliance, please go to [Exabeam Community](#) for more information or create a ticket for more assistance.



Server Configurations	
Model	Supermicro SuperServer SYS-1019P-WTR
Motherboard	Super X11SPW-TF
CPU	Intel Xeon Silver 4210 2.2Ghz <ul style="list-style-type: none"> • 10 cores/ 20 threads with 2.2 GHz base frequency and 13.75 MB cache
Memory	128 GB (DDR4) <ul style="list-style-type: none"> • 4 x 32 GB • Micron 32 GB 2666MHz ECC Reg Z01B

Server Configurations	
Storage	2 x 240 GB (SSD) <ul style="list-style-type: none"> • 2.0 DWPD, SATA3, 2.5 in • Intel S4510 240 GB 2 x 3.84 TB (SSD) <ul style="list-style-type: none"> • 3.0 DWPD, SATA, 2.5 in • Samsung SM883 3.84 TB 6 x 2 TB (HDD) <ul style="list-style-type: none"> • 7200 RPM, 2.5 in • Seagate 7E200 EC2.5 2TB SATA 512E
Chassis Configuration	23.5" Depth 1U Rackmount Chassis <ul style="list-style-type: none"> • 10 drive bays (2.5 in)
Network Controller	2 x 10 Gbps (RJ45) LAN 1 x dedicated IPMI

Server Dimensions	
Height	1.7" (43.7 mm)
Width	17.2" (437 mm)
Depth	23.5" (597 mm)
Packaging	8" (H) x 24" (W) x 32" (D) 203 mm (H) x 610 mm (W) x 813 mm (D)
Gross Weight	27 lbs (12.25 kg)
Net Weight	15.5 lbs (7.03 kg)

Operating Environment (System)		
	Operating	Non-Operating
Heat Output	599.49 BTU/hr	281.49 BTU/hr
Temperature Range	10°C - 35°C (50°F - 95°F)	-40°C - 60°C (-40°F - 140°F)
Relative Humidity Range (non-condensing)	8% - 90%	5% - 95%

Power Supply	
500W Redundant Power Supplies with PMBus	
AC Voltage	100-240Vac, 50-60Hz, 6.1-2.6A
+5V Standby	Max: 4A / Min: 0A
+12V	Max: 42A / Min: 0.5A

Certifications	
Power Supply Safety / EMC	80 PLUS Platinum Certified